FIBRE DISTRIBUTION BOX

FTTx & FTTA 24 / 48F IP66 EXTERNAL



CODECOM fibre optic distribution box can accomodate the termination of up to 2 fibre cables, offers spaces for a splitter module and or splicing and adapters for external environments.

An ideal solution for a provider of FTTx or FTTA Wireless networks.

The fibre distribution box is specifically designed to be flexible to suit varying applications and is both wall or pole mountable. The box body structure, has a specific function to guard against theft or damage to the internal assets.

Features & Applications

- IP66 Rated Dust & Waterproof (UV Resistant)
- · Light & Robust PVC construction
- Lockable with Excellent Sealing
- Flexible Splice, Splitter or Breakout
- 24F SC/PC Simplex or 48F LC/PC Duplex
- Wall or Pole Mount
- Port Labelling
- · Custom Branding Available





GENERAL SPECIFICATIONS

PARAMETERS	VALUE	PARAMETERS	VALUE
Height	340mm	Depth	110mm
Width	250mm	Operating Temp	-40°C/+85°C
Housing Material	ABS & PC	Humidity	85% above @ 30°C
Weight	3kg	Air Pressure	70kPa - 106kPa
Warranty	12 Months	Accessories	Adapters, Pigtails, Splice Tray & Protecto









