


**FIBRE MANAGEMENT**

# MicroCore Flex Armoured Fibre Cable - up to 24 core



Codecom Indoor / Outdoor Microcore Flex Armoured fibre cable contains up to 24 fibres of 250µm in a micro tube.

Fibres are housed in the helical flex armoured tube, then with aramid yarn added in the cable to make ideal use in the indoor/outdoor environment where additional protection is required.

## Features

- ✓ Conform to IEC, EIA-TIA, and Telcordia performance requirements
- ✓ Standard SM and MM fibres available
- ✓ Compact cable construction
- ✓ Individually coloured optical fibres

## Applications

- ✓ Suitable for internal & external applications
- ✓ Suitable for environments where impact protection is required

## Specifications

Parameters	Units	Value	
Fiber Count		12FO	24FO
Outer Jacket Diameter	mm	4.5±0.1	
Micro Tube Diameter	mm	1.5±0.1	2.0±0.1
Flex Armored Tube Diameter	mm	2.8±0.2	
Strength Member		Aramid Yarn	
Tensile Strength (Long Term)	N	100	
Tensile Strength (Short Term)	N	400	
Crush Resistance (Long Term)	N/100mm	500	
Crush Resistance (Short Term)	N/100mm	1000	
Min. Bending Radius	mm	10D (static)/20D (dynamic)	
Storage Temperature	°C	-40 ~ +70	
Installation Temperature	°C	-10 ~ +50	
Nominal Cable Weight	KG/KM	29	31

## Fibre Colours

1	2	3	4	5	6
Blue	Orange	Green	Brown	Grey	White
7	8	9	10	11	12
Red	Black	Yellow	Violet	Pink	Aqua